

EARLOUGHER ENGINEERING SUMMARY OF CORE ANALYSIS DATA

COMPANY Producers, Finston & Gore

LEASE

S. Baptist

WELL NO. W-43

Sec.	Formation	Depth, Ft.		Net Ft. of Sand	Avg. Por.	Avg. Core Saturation		Core Oil Content		Permeability		Flood Pot Residuals			Oil Recovery Bbl./Ac.		
		From	To			Oil	Water	Avg. S/A, Ft.	Total B/Ac.	Avg. Md.	Capacity Ft. x Md.	Saturation		Oil Content		Diff.	Flood Pot
												Oil	Water	B/A, Ft.	B/Ac.		
1	LONE GROVE NO. 2	1095.0	1099.0	4.0	17.6	14.	72.	188.	750	1.9	7.5	--	--	--	--		
2		1092.0	1111.0	12.0	17.2	7.7	74.	107.	1,290	1.9	13.	--	--	--	--		
1-2		7	1095.0	111.0	16.0	17.8	9.2	74.	128.	2,040	1.3	20.5	--	--	--	--	

EARLOUGHER ENGINEERING

RESULTS OF SATURATION TESTS

COMPANY Producers, Finston & Gore

WELL S. Baptista No. W-43

Sat. No.	Depth Feet	Porosity Per Cent	Per Cent Saturation			Avg. Oil Content Bbl./A. Ft.	Feet of Sand		Total Oil Content Bbl./Acres
			Oil	Water	Total		Ft.	Cum.	
1	1095.9	19.1	14.	63.	77.	200.	1.0	1.0	200.
2	1096.6	17.7	14.	68.	82.	200.	1.0	2.0	200.
3	1097.6	16.7	11.	83.	94.	140.	1.0	3.0	140.
4	1098.4	17.0	16.	74.	90.	210.	1.0	4.0	210.
5	1099.2	16.6	7.8	79.	87.	100.	1.0	5.0	100.
6	1100.5	16.1	11.	77.	88.	140.	1.0	6.0	140.
7	1101.3	17.3	7.5	77.	85.	100.	1.0	7.0	100.
8	1102.2	16.2	6.7	78.	85.	85.	1.0	8.0	85.
9	1103.2	19.9	6.4	73.	79.	100.	1.0	9.0	100.
10	1104.3	17.0	7.8	83.	91.	100.	1.0	10.0	100.
11	1105.2	18.8	6.9	63.	70.	100.	1.0	11.0	100.
12	1106.2	18.6	7.0	71.	78.	100.	1.0	12.0	100.
13	1107.2	18.8	7.4	68.	75.	110.	1.0	13.0	110.
14	1108.2	17.9	10.	75.	85.	130.	1.0	14.0	130.
15	1109.1	19.0	7.8	68.	76.	110.	2.0	16.0	220.

rb

EARLOUGHER ENGINEERING
RESULTS OF PERMEABILITY TESTS

COMPANY Producers, Finston & Gore

WELL S. Baptiste No. W-43

Sample No.	Depth Feet	Permeability Millidarcys	Feet of Sand		Capacity Ft. X Md.	Sample No.	Depth Feet	Permeability Millidarcys	Feet of Sand		Capacity Ft. X Md.
			Fi.	Cum. Ft.					Fi.	Cum. Ft.	
1-A	1095.5	5.7	0.5	0.5	2.8	9	1103.2	3.0	0.5	8.5	1.5
1	1095.9	0.9	0.5	1.0	0.5	9-A	1103.8	1.1	0.5	9.0	0.6
2-A	1096.3	2.8	0.5	1.5	1.4	10	1104.3	0.6	0.5	9.5	0.3
2	1096.6	0.3	0.5	2.0	0.2	10-A	1104.9	0.3	0.5	10.0	0.2
3-A	1097.4	1.3	0.5	2.5	0.7	11	1105.2	0.3	0.5	10.5	0.2
3	1097.6	1.6	0.5	3.0	0.8	11-A	1105.8	1.0	0.5	11.0	0.5
4-A	1098.0	1.6	0.2	3.2	0.3	12	1106.2	0.3	0.3	11.3	0.1
4	1098.4	0.6	0.5	3.7	0.3	12-A	1106.5	0.9	0.7	12.0	0.6
5-A	1098.9	1.6	0.3	4.0	0.5	13	1107.2	0.9	0.5	12.5	0.5
5	1099.2	1.3	0.5	4.5	0.7	13-A	1107.7	0.9	0.5	13.0	0.5
6-A	1099.6	0.3	0.5	5.0	0.2	14	1108.2	3.9	0.5	13.5	2.0
6	1100.5	1.4	1.3	6.3	1.8	14-A	1108.8	0.3	0.5	14.0	0.2
7	1101.3	0.1	0.3	6.6	0.1	15	1109.1	0.5	0.2	14.2	0.1
8	1102.2	1.0	0.9	7.5	0.9	15-A	1109.3	0.9	0.8	15.0	0.7
8-A	1102.6	1.0	0.5	8.0	0.5	16-A	1110.7	1.1	1.0	16.0	1.1

rb